\A/+ 0/_



Rich Body Butter Plus Sunscreen No. 603

		VV1.70
	VEEGUM [®] Ultra Magnesium Aluminum Silicate	1.0
Α	VANZAN [®] NF Xanthan Gum	0.5
	Water	58.5
	Glycerin	3.0
	Sorbeth-30	2.0
в	C12-15 Alkyl Benzoate (Finsolv [®] TN ¹)	2.0
	Dimethicone (XIAMETER [®] PMX-200 Silicone Fluid 350 cs ²)	1.0
	Soybean (Glycine Soja) Oil (Super Refined [®] Soybean USP ³)	2.5
	Butyrospermum Parkii (Shea) Butter (Tomasa Shea Butter ⁴)	3.5
	Isopropyl Myristate (and) Glycine Soja (Soybean) Oil (and) Retinyl	1.0
	Palmitate (and) Carthamus Tinctorius (Safflower) Seed Oil (and) Linoleic	
	Acid (and) Tocopherol (Vitamin Complex AEF OS ³)	
	Stearyl Alcohol (Lanette [®] 18 ⁵)	5.0
	Glyceryl Stearate (and) PEG-100 Stearate (Arlacel [®] 165 ³)	5.0
	C12-15 Alkyl Benzoate (and) Titanium Dioxide (and) Aluminum Stearate	15.0
	(and) Polyhydroxystearic Acid (and) Alumina (Solaveil [®] CT-100 ³)	

C Preservative

Procedure: While heating the water to 70-75°C, slowly add the **VEEGUM**[®] *Ultra* and **VANZAN**[®] **NF** sequentially or as a dry blend to the water agitated at maximum available shear. Mix until fully hydrated. Add the remaining water phase ingredients, mixing until uniform. Maintain the water phase at 70-75°C. Combine Part B ingredients and heat to 70-75°C. Add the oil phase to the water phase with good agitation; mix until uniform. Cool with mixing; add Part C when the emulsion is <30°C. If necessary, adjust the pH to 6.5 ± 0.5 .

RAW MATERIAL SUPPLIERSTRADEMARKS¹Innospec Active Chemicals, Edison, NJVEEGUM and VANZAN are registered trademarks of Vanderbilt Minerals, LLC.²Dow Corning Corporation, Midland, MIArlacel is a registered trademark of Uniqema Americas LLC.³Croda, Inc., Edison, NJFinsolv is a registered trademark of Innospec Performance Chemicals Company.⁴Tri-K Industries, Inc., Northvale, NJLanette is a registered trademark of Cognis IP Management GmbH.⁵BASF Care Creations, Florham Park, NJSolaveil is a registered trademark of Croda International PLC.Super Refined is a registered trademark of Croda, Inc.

Xiameter is a registered trademark of Dow Corning Corporation.

Rev04/25/2013

q.s.

Before using, read, understand and comply with the information and precautions in the Safety Data Sheets, label and other product literature. The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all-inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. Vanderbilt Minerals, LLC does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent, trademark or copyright or to violate any federal, state or local law or regulation.