

Stay Dry W/O Antiperspirant Stick No. 341

		Wt. %
A	VEEGUM® HV Magnesium Aluminum Silicate	1.0
	Water	20.0
	Aluminum Chlorhydrate, impalpable	18.0
B	Cyclomethicone (Dow Corning® ST-Cyclomethicone-5 NF ¹)	26.0
	Isopropyl Myristate	5.0
	Stearyl Alcohol	24.0
	Sorbitan Trioleate (Span® 85 ²)	5.0
	Polysorbate 85 (Tween® 85 ²)	1.0
C	Preservative	q.s.

Procedure: While heating the water to 65-70°C, slowly add the **VEEGUM HV** to the water agitated at maximum available shear. Mix until fully hydrated. Add the aluminum chlorhydrate and mix until uniform, maintaining to 65-70°C. Heat Part B to 65-70°C. Add Part A to Part B with good agitation. Cool with mixing to 50-55°C. Add Part C and pour into molds to cool.

RAW MATERIAL SUPPLIERS

¹Dow Corning Corporation, Midland, MI
²Uniqema, New Castle, DE

TRADEMARKS

VEEGUM is a registered trademark of Vanderbilt Minerals, LLC.
Dow Corning is a registered trademark of Dow Corning Corporation.
Span and Tween are registered trademarks of Uniqema Americas LLC.

Rev01/30/2013